



- A. 0.080" thick, 1.50" wide, dual layer rubber, black conductive exterior with a non-marring interior. Tear resistant nylon reinforced 4.3 oz. inner scrim layer prevents the rubber from tearing.
- B. 3/8" wide, 30" long blue polyester tab contains electrically conductive carbon suffused fibers.
- C. 3/4" wide blue elastic material stretches for comfort.
- D. Adjustable snap-loc fastening system.
- E. A 1/4 watt, 2 megohm resistor.
- F Stretch elastic back.

(I) listed and date coded.

Electrical Properties Property

Flooring contact surface (sole) to body contacting surface (tab) resistance.

Test MethodANSI/ESD STM97.1, ESD SP9.2, < 1 x 10⁹ ohms
ESD TR53

RoHS 2, REACH, and Conflict Minerals Statement
None of the RoHS 2 restricted materials, or REACH substances of very high
concern as of 2015/06/15, or Conflict Minerals are intentionally added in
manufacturing this product. Ref: European Union Directive 2011/65/EU and
Regulation (EC) No. 1907/2006/CE. See Desco Limited Warranty at Desco.com.

For additional information on the use and maintenance of foot grounders please ask for Technical Bulletin $\underline{\text{TB-2020}}$.

Item	<u>17239</u>	<u>17240</u>	<u>17241</u>	<u>17242</u>	<u>17243</u>
Size	XSmall	Small	Medium	Large	XLarge
Shoe Size Women	5 - 7	6 - 8	7 - 9	8 - 11	11+
Shoe Size Men	N/A	6 - 9	8 - 11	10 - 13	12+

Recommended sizing. Request samples HERE.



United States of America

Specifications and procedures subject to change without notice.



DESCO WEST: 3651 WALNUT AVE., CHINO, CA 91710
WEB SITE: Desco.com PHONE (909) 627-8178 FAX (909) 627-7449
DESCO FAST: ONE COL GATE WAY, CANTON, MA 02021-1407

DESCO EAST: ONE COLGATE WAY, CANTON, MA 02021-1407 PHONE (781) 821-8370 FAX (781) 575-0172

SOLE GROUNDER WITH SNAP-LOC

DRAWING NUMBER 17239 DATE: January 2016